



AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200
SDS Reference Number: SDS.01
Issue date: 9/11/2023 Revision date: 11/14/2025 Version: 0.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : AFCAT DOOR & WINDOW PU GUN FOAM
Type of product : Aerosol
Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Aerosol
Polyurethane Foam

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Importer

AFCAT Group, INC
4520 S Buckner Blvd. Ste A,
Dallas, TX. 75227
Phone.: 469 – 678 - 1008
sales@afcatusa.com - www.AFCATUSA.com

1.4. Emergency telephone number

Emergency number : 911 | INFOTRAC: 1-800-535-5053

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

NFPA:

Health Hazards: 2
Flammability Hazards: 4
Instability Hazards: 1
Special Hazards: Non-applicable

29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Aerosol, Category 1	H222;H229
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Full text of H statements : see section 16	

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet


according to 29 CFR 1910.1200

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements

NFPA:



29 CFR 1910.1200:

Hazard pictograms



Signal word

Contains

Hazard statements

: Danger
: 4,4' diphenylmethanediisocyanate, isomere, homologue and mixtures
: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
: EUH204 - Contains isocyanates. May produce an allergic reaction.

Precautionary statements

EUH-statements

2.3. Other hazards

Contains PBT&vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

3.2. Mixtures

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. Exact percentage values for components are proprietary in accordance with 29 CFR 1910.1200(i). Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Name	Product identifier	%
4,4' diphenylmethanediisocyanate, isomere, homologe and mixtures (Note 2)(Note C)	CAS-No.: 9016-87-9 EC-No.: 618-498-9	25 – 55
Reaction products of phosphoryl trichloride and 2-methyloxirane	CAS-No.: 1244733-77-4 EC-No.: 807-935-0	10 – 30
isobutane (Note C)(Note U)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0	2 – 15
dimethyl ether (Note U)	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8	2 – 15
propane (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5	2 – 15
2,2'-dimorpholinyl-diethyl ether	CAS-No.: 6425-39-4 EC-No.: 229-194-7	0.1 – 5

Specific concentration limits:

Name	Product identifier
4,4' diphenylmethanediisocyanate, isomere, homologe and mixtures	CAS-No.: 9016-87-9 EC-No.: 618-498-9

- Note 2: The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.
- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. No flames, no sparks. Eliminate all sources of ignition. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Stop leak if safe to do so. Do not allow contact with air. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Absorb spillage to prevent material damage. Isolate from fire, if possible, without unnecessary risk. Eliminate every possible source of ignition. Use special care to avoid static electric charges. No open flames. No smoking. Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area. Evacuate unnecessary personnel. Stop leak if safe to do so. Stop release. Use grounded electrical/mechanical equipment. Keep away from combustible material. All equipment used when handling the product must be grounded.

6.2. Environmental precautions

Avoid release to the environment. Avoid discharge to atmosphere. Do not allow water (or moist air) contact with this material. Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Do not allow product to spread into the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Consult an expert on waste disposal or treatment.
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Flammable gas. Do not pierce or burn, even after use. Handle empty containers with care because residual vapours are flammable. May explode on heating.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: 0 – 30 °C
Storage area	: Store away from heat. Store in a well-ventilated place.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Dimethyl ether (115-10-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	1894 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	471 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.155 mg/l
PNEC aqua (marine water)	0.016 mg/l
PNEC aqua (intermittent, freshwater)	1549 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.681 mg/kg dwt
PNEC sediment (marine water)	0.069 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.045 mg/kg dwt

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

Dimethyl ether (115-10-6)

PNEC (STP)

PNEC sewage treatment plant	160 mg/l
-----------------------------	----------

2,2'-Dimorpholinodiethyl ether (6425-39-4)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	7.28 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	0.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.8 mg/m ³
Long-term - systemic effects, dermal	0.5 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater)	0.1 mg/l
PNEC aqua (marine water)	0.01 mg/l
PNEC aqua (intermittent, freshwater)	1 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	8.2 mg/kg dwt
PNEC sediment (marine water)	0.82 mg/kg dwt

PNEC (Soil)

PNEC soil	1.58 mg/kg dwt
-----------	----------------

PNEC (Oral)

PNEC oral (secondary poisoning)	10 mg/kg food
---------------------------------	---------------

PNEC (STP)

PNEC sewage treatment plant	100 mg/l
-----------------------------	----------

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Light yellow
Appearance	: Aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable, as aerosol.(≤50°C)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not miscible.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 15 – 18 kg/m ³ @23°C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 45 %

9.2.2. Other safety characteristics

Ideal Can Temperature : 20 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

AFCAT DOOR & WINDOW PU GUN FOAM	
ATE CLP (dust,mist)	3 mg/l/4h

AFCAT DOOR & WINDOW PU GUN FOAM	
ATE (dust,mist)	2.727 mg/l/4h

2,2'-Dimorpholinodiethyl ether (6425-39-4)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Remarks on results: other:
LD50 dermal rabbit	3038 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.

4,4' diphenylmethanediisocyanate, isomere, homologue and mixtures (9016-87-9)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

4,4' diphenylmethanediisocyanate, isomere, homologue and mixtures (9016-87-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

2,2'-Dimorpholinodiethyl ether (6425-39-4)	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

Aspiration hazard	: Not classified
-------------------	------------------

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

AFCAT DOOR & WINDOW PU GUN FOAM

Vaporizer

Aerosol

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

Dimethyl ether (115-10-6)

LC50 - Fish [1] > 4.1 g/l Test organisms (species): Poecilia reticulata

EC50 - Crustacea [1] > 4.4 g/l Test organisms (species): Daphnia magna

EC50 96h - Algae [1] 154917 mg/l Test organisms (species): other:

2,2'-Dimorpholinodiethyl ether (6425-39-4)

LC50 - Fish [1] > 2337.5 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)

EC50 - Crustacea [1] > 100 mg/l Test organisms (species): Daphnia magna

EC50 72h - Algae [1] > 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations. Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.






AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
DOT Classification				
UN 1950 Hazard Class: 2.1				
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Title III - Toxic Chemical Release Inventory Reporting (Section 313): 4,4'-methylenediphenyl diisocyanate, isomers and homologues

California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986): Non-applicable

The Toxic Substances Control Act (TSCA) : 4,4'-methylenediphenyl diisocyanate, isomers and homologues ; Propane-1,2-diol, propoxylated ; Glycerol, propoxylated ; Isobutane ; 1,1-difluoroethane ; Dimethyl ether ; Propane

Massachusetts RTK - Substance List: 4,4'-methylenediphenyl diisocyanate, isomers and homologues

New Jersey Worker and Community Right-to-Know Act: 4,4'-methylenediphenyl diisocyanate, isomers and homologues ; Isobutane ; 1,1-difluoroethane ; Dimethyl ether ; Propane

New York RTK - Substance list: Isobutane ; 1,1-difluoroethane ; Dimethyl ether ; Propane

Pennsylvania Worker and Community Right-to-Know Law: Isobutane ; Dimethyl ether ; Propane

NTP (National Toxicology Program): Non-applicable

Hazardous substances release notification under CERCLA sections 102-103 (40 CFR Part 302): Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The Toxic Substances Control Act (TSCA)

SARA Title III - Community Right-to-Know Reporting Requirements (Sections 311-312)

SARA Title III - Toxic Chemical Release Inventory Reporting (Section 313)

Emergency Planning and Community Right-to-Know Act (EPCRA) Reportable Quantities

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

Abbreviations and acronyms:

NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources

: ECHA (European Chemicals Agency). Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
EUH204	Contains isocyanates. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

AFCAT DOOR & WINDOW PU GUN FOAM

Safety Data Sheet

according to 29 CFR 1910.1200

Full text of H- and EUH-statements:

H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
Press. Gas	Gases under pressure
Press. Gas (Diss.)	Gases under pressure : Dissolved gas
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS),

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable