



AFCAT WINTER GUN (BLACK OEM) FOAM

Technical Data Sheet

Issue date: 5/22/2024 Revision date: 11/14/2025

Version: 0.1

TDS No.: TDS.05

1. Product Description

Product description	: AFCAT WINTER GUN (BLACK OEM) FOAM is a multi-purpose specially formulated to yield extra volume, moisture cured installation and filling foam.
Product form	: Mixture
Trade name	: AFCAT WINTER GUN (BLACK OEM) FOAM
Use of the substance/mixture	: Polyurethane Foam
Recommended use	: Industrial use Professional uses Consumer use
Type of product	: Aerosol
Vaporizer	: Aerosol

2. Characteristics

Characteristics	: Resistant against all kinds of weather conditions, seawater, steam and humidity
-----------------	---

3. Application

- Fixing doors, windows and similar frames
- Using in insulation of hot and cold water pipes and electrical equipments
- Fixing the gaps, holes and cracks
- Bonding to all kinds of building materials except silicone, teflon, polyethylene and polypropylene

4. Application Instructions

- Application temperature is between -15 °C to +30 °C
- Shake the can strongly for 30 seconds
- Install the foam gun on the can
- Remove the dirt, dust and grease from the application place
- Turn the can upside down and press trigger
- Moisturising the ground and released foam is strongly advised
- Moisturising accelerates reaction and ensures a productive result
- For later applications, dried foam residue should be removed from the gun and valve
- Fresh foam residue can be cleaned by using PU FOAM CLEANER
- Cured Foam can be cleaned mechanically
- Since foam tends to expand, proper quantities should be used
- Can be shaved, sandpapered and painted after it get hardens in 1 or 3 hours

5. Technical Specifications (@ 23 °C 50% RH)

Physical state	: Liquid
Chemical Basis	: Polyurethane Prepolymer.
Appearance	: Aerosol.
Colour	: Black
Odour	: characteristic
Curing System	: Moisture
Skin Forming Time (FEICA TM1014)	: 8 – 10 minutes
Cutting Time (FEICA TM1005)	: 45 – 60 minutes
Density	: 17 - 20 kg/m ³
Flash point	: Not applicable, as aerosol.(≤ 50°C)
Thermal Resistance	: -40 – 100 °C



AFCAT WINTER GUN (BLACK OEM) FOAM

Technical Data Sheet

Issue date: 5/22/2024 Revision date: 11/14/2025

Version: 0.1

TDS No.: TDS.05

Yield (FEICA TM1003)	: 40 - 50 l
Application Temperature	: -15 → 30 °C
Ideal Can Temperature	: 20 °C

The manufacturer uses test methods approved by FEICA designed to deliver transparent and reproducible test results, ensuring customers have an accurate representation of product performance. FEICA OCF test methods are available at: <http://www.feica.com/our-industry/pu-foam-technology-ocf>. FEICA is a multinational association representing the European adhesive and sealant industry, including one-component foam manufacturers. Further information at: www.feica.eu

6. Packaging

Packaging	: Aerosol Original packaging
Packaging	: Aerosol.
Colour	: black

Canister 680 g / 24 oz	Package 12 pcs/ctn
------------------------	--------------------

7. Shelf Life and Storage

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: -5 → 30 °C

Canister 680 g / 24 oz	18 months (after production date if stored at room temperature)
------------------------	---

8. Health and Safety

Additional information	: Keep away from children Product Safety Data Sheet must be read and understood before use. These documents are available on request. Protective gloves Avoid contact with eyes Avoid contact with skin and eyes
Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Other medical advice or treatment	: Treat symptomatically.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.



AFCAT WINTER GUN (BLACK OEM) FOAM

Technical Data Sheet

Issue date: 5/22/2024 Revision date: 11/14/2025

Version: 0.1

TDS No.: TDS.05

9. Remarks

Remarks : For further information, please refer to the Safety Data Sheet

10. Standards and Certificates

No information available

Technical Data Sheet

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable