

Safety Data Sheet
acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

* **1 Identification**

- **Product identifier**
- **Trade name:** ElastiSeal® BP-300 White
- **Article number:** 730451
- **Relevant identified uses of the substance or mixture.** Sealant
- **Application of the substance / the mixture** Sealant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Royal Adhesives & Sealants, LLC
4401 Page Avenue. P. O. Box 457
Michigan Center, MI 49254
Information Phone Number: 517-764-0334
- **Information department:** Environment protection department.
- **Emergency telephone number:**
ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

* **2 Hazard(s) identification**

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard statements**
Causes skin irritation.
Causes serious eye irritation.
- **Precautionary statements**
Wear protective gloves.
Wear eye protection / face protection.
Wash thoroughly after handling.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Specific treatment (see on this label).
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: **ElastiSeal® BP-300 White**

(Contd. of page 1)

If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	2	Fire = 2
PHYSICAL HAZARD	0	Physical Hazard = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Hazardous components:**

471-34-1	calcium carbonate	25-50%
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	5-20%
1332-58-7	Kaolin	2.5-10%
8052-41-3	Stoddard solvent (mineral spirits)	2.5-10%
546-93-0	Magnesite	2.5-10%
1317-65-3	Limestone	2.5-10%
13463-67-7	titanium dioxide	≤2.5%
112926-00-8	Precipitated silica (Silica-Amorphous)	≤2.5%
1305-78-8	calcium oxide	≤2.5%
68953-58-2	organoclay [containing 0-3% quartz CAS 14808-60-7]	≤1.0%
	Amorphous Fumed Silica	≤0.5%
14808-60-7	Quartz (SiO ₂)	≤0.03%

- **Additional information:**

All concentrations are in percent by weight unless the ingredient is a gas. Gas concentrations are in percent by volume. Any pigments or fillers in this product which may be considered "Hazardous" are potentially hazardous only if inhaled as an airborne dust. Exposure by these ingredients as used in sealants, putties, bedding compounds and non-sprayable products is highly unlikely. For the wording of the listed risk phrases refer to section 15.

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Call a doctor immediately.
Overexposure, remove to fresh air and seek medical attention.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: ElastiSeal® BP-300 White

(Contd. of page 2)

- **After skin contact:**
Wipe excess from skin.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Protective clothing and respiratory protective device.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- **Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep container closed when not in use.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Keep away from open flames and high temperatures.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: **ElastiSeal® BP-300 White**

(Contd. of page 3)

· **Control parameters**· **Components with limit values that require monitoring at the workplace:****471-34-1 calcium carbonate**PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV TLV withdrawn

1332-58-7 KaolinPEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 2* mg/m³

E; as respirable fraction

8052-41-3 Stoddard solvent (mineral spirits)PEL Long-term value: 2900 mg/m³, 500 ppm

REL Long-term value: 350 ppm

Ceiling limit value: 1800* mg/m³

*15-min

TLV Long-term value: 525 mg/m³, 100 ppm**546-93-0 Magnesite**PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV TLV withdrawn

13463-67-7 titanium dioxidePEL Long-term value: 15* mg/m³

*total dust

REL See Pocket Guide App. A

TLV Long-term value: 10 mg/m³

withdrawn from NIC

112926-00-8 Precipitated silica (Silica-Amorphous)PEL 20mppcf or 80mg/m³ /%SiO₂REL Long-term value: 6 mg/m³

See Pocket Guide App. C

TLV TLV withdrawn

1305-78-8 calcium oxidePEL Long-term value: 5 mg/m³REL Long-term value: 2 mg/m³TLV Long-term value: 2 mg/m³**14808-60-7 Quartz (SiO₂)**

PEL see Quartz listing

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: ElastiSeal® BP-300 White

(Contd. of page 4)

REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Protective gloves.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Pasty

Color: White

· **Odor:** Hydrocarbon-like

· **Odour threshold:** Not determined.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: **ElastiSeal® BP-300 White**

(Contd. of page 5)

· pH-value:	Not applicable.
· Change in condition	
Melting point:	Undetermined.
· Boiling point:	
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	230 °C (446 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Flammable limits:	
Lower:	1.1 Vol %
Upper:	6.0 Vol %
· Vapor pressure:	Not applicable.
· Specific gravity at 20 °C (68 °F):	1.4 g/cm ³ (11.683 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not applicable.
· Solubility in / Miscibility with	
Water:	Insoluble
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	>20.5cSt
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	85.0 %
· Other information	VOC < 150 g/l

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flames, sparks.
- **Incompatible materials:** Reacts with strong oxidizing agents.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** May irritate the skin.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: ElastiSeal® BP-300 White

(Contd. of page 6)

- **on the eye:** May irritate the eye.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Due to the form of this product, exposure to the potentially carcinogenic components is not expected.
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
112926-00-8	Precipitated silica (Silica-Amorphous)	3
14808-60-7	Quartz (SiO ₂)	1
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** Not expected to be harmful to aquatic organisms
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Small amounts can be disposed of with household waste after the product has cured or skinned over. Larger quantities should be disposed of according to state and local regulation.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, ADN, IMDG, IATA** not regulated
- **UN proper shipping name**
- **DOT, ADR, ADN, IMDG, IATA** not regulated

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: **ElastiSeal® BP-300 White**

(Contd. of page 7)

· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	not regulated
· Packing group	
· DOT, ADR, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	This product is not classified as a Division 4.1 Flammable Solids according to UN Test N.1 Test Method for Readily Combustible Solids.
· UN "Model Regulation":	-

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

100-41-4 ethylbenzene

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Domestic Substance List

All components of this product are on the DSL (Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

100-41-4 ethylbenzene

D

· TLV (Threshold Limit Value established by ACGIH)

1332-58-7 Kaolin

A4

13463-67-7 titanium dioxide

A4

14808-60-7 Quartz (SiO₂)

A2

100-41-4 ethylbenzene

A3

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/10/2015

Revision Number 2

Revision Date 07/10/2015

Trade name: ElastiSeal® BP-300 White

(Contd. of page 8)

· MAK (German Maximum Workplace Concentration)		
13463-67-7	titanium dioxide	3A
14808-60-7	Quartz (SiO ₂)	I
100-41-4	ethylbenzene	3A
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO ₂)	

· **National regulations:**

· **Water hazard class:** Not determined.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **Department issuing SDS:** Environment protection department.

· **Creation Date:** 01/26/2015

· **Date of preparation / last revision** 07/10/2015 / 1

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

USA