

AFCAT Vinyl Seaming Tape VST-3150

WHITE EMBOSSED PVC Tape

DESCRIPTION

Adopts white color embossed PVC film as backing, combined with a high performance solvent acrylic adhesive, It is mainly used for rubber foam packaging and sealing.

TYPICAL PHYSICAL PROPERTIES

PROPERTIES	METRIC	TEST METHOD
Total Thickness	180 Microns	PSTC-133 / ASTM D 3652
Adhesion to Steel	18 N/25mm	PSTC-101 / ASTM D 3330
Rolling Tack	10 mm	PSTC-6 / ASTM D 3121
Service Temperature	-20 ~ +60 °C	-----
Applying Temperature	+10 ~ 40 °C	-----

IMPORTANT NOTE

1. The data above are typical values only, and should not be used for specifications purpose.
2. Tolerance: Weight and Thickness: $\pm 10\%$; Width: $\pm 3\text{mm}$; Length: Cut Roll: $\pm 0.3\text{m}$, Jumbo Roll $\pm 0.5\%$.

STORAGE & SHELF LIFE: 12 months when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

SURFACE PREPARATION: It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

PRODUCT USE: It is essential that the user evaluate our product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on our products between +10 ~ +40°C (+50 ~ +105 °F).
