

# GreenGuard<sup>®</sup>

## Seam Tape

For use to seal seams on building wrap and insulation.



- Seals seams on building wrap and insulation
- 1 7/8" Standard Seam Tape for general applications
- 2 7/8" Custom Seam Tape for uneven surfaces and enhanced adhesion

# GreenGuard®

## Seam Tape

### Description

Kingspan GreenGuard® Seam Tape is self-adhering tape comprising a polyolefin film with an acrylic adhesive.

Kingspan GreenGuard® Seam Tape adds an extra layer of air and moisture protection to structures. 1 7/8" wide Kingspan GreenGuard® Seam Tape is recommended for flat surfaces. 2 7/8" wide Kingspan GreenGuard® Custom Seam Tape is recommended for uneven surfaces, such as Kingspan GreenGuard® RainDrop® 3D Building Wrap and Kingspan GreenGuard® RainArmor™. Both tapes stick tight in all seasons, even when the temperature drops below freezing. Long-lasting UV stabilizers help them resist the deteriorating effects of the sun. The tapes can also be used to repair rips in damaged insulation and building wrap, eliminating waste and saving money.

### Installation

Placement by hand, then it is necessary to apply strong pressure with a j-roller to ensure adhesion.

### Compliance

Intertek CCRR-1018

(for use with Kingspan GreenGuard® Building Wrap);

Intertek CCRR-1022 (for use with Kingspan GreenGuard® Siding Underlayment & Sheathing);

Intertek CCRR 1021 (for use with Kingspan GreenGuard® XPS Insulation Board).

### Handling & Storage

Store boxes containing Kingspan GreenGuard® Seam Tape in a clean, dry area without prolonged, direct exposure to sunlight. Seam Tape has a shelf life of 12 months.



Please scan the QR code for the most recent product information.

### Kingspan Insulation LLC

2100 Riveredge Parkway | Suite 175  
Atlanta | Georgia 30328

T: +1 (800) 241 4402 F: +1 (678) 589 7325

E: [info@kingspaninsulation.us](mailto:info@kingspaninsulation.us)

[www.kingspaninsulation.us](http://www.kingspaninsulation.us)

© Kingspan, the G Device and the Lion Device are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. All rights reserved.

© GreenGuard is a Registered Trademark of the Kingspan Group plc in the US. All rights reserved.

kingspan-green-guard-seamtape-product-data-sheet-en-us-v4.1

Version 4.1 - 04/2023

Product Data		
Property	Kingspan GreenGuard® Standard Tape	Kingspan GreenGuard® Custom Seam Tape
General		
Nominal Width (in)	1 7/8	2 7/8
Nominal Thickness (in)	0.003	0.004
Color	Clear / Green	Mint Green / Green
Backing Material	Polypropylene	Polypropylene
Adhesive	Acrylic	Acrylic
Adhesion to Steel (oz/in)	50	70
Recommended Service Temp. (°F)	- 40 to 185	- 40 to 185
Application Temperature (°F)	10 to 110	10 to 110
Shelf Life (yr) (from date of purchase)	1	1

For more information on specific building product recommendations and installation guidelines, contact your Kingspan Insulation LLC representative.

Kingspan Insulation LLC believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Kingspan Insulation LLC does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. No warranty, express or implied, is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the products referred to.

